

Attestation of Conformity

No. E8A 18 03 03649 002

Holder of Certificate: Zhejiang CHINT

Instrument & Meter Co., Ltd.

Wenzhou Bridge Industrial Zone

325603 Yueging

PEOPLE'S REPUBLIC OF CHINA

Name of Object: **Power meters**

(Single-Phase Smart Meter)

Model(s): **DDSU666**

Description of

Object:

Rated voltage: Rated current:

230V, 50/60 Hz 5(80)A, 1.5(6)A

Protection class:

Tested according to:

EN 61326-1:2013 EN 61326-2-1:2013

This Attestation of Conformity is issued on a voluntary basis according to the Directive 2014/30/EU relating to electromagnetic compatibility. It confirms that the listed apparatus complies with all essential requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. See also notes overleaf.

Test report no.: 64713180109701





Date, 2018-04-09

(Tony Liu)



After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. That declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed

Page 1 of 1

A1 / 07.17



Attestation of Conformity

No. N8A 18 04 03649 005

Holder of Certificate: Zhejiang CHINT

Instrument & Meter Co., Ltd.

Wenzhou Bridge Industrial Zone

325603 Yueging

PEOPLE'S REPUBLIC OF CHINA

Product: Electronic measuring equipment

(Single-Phase Smart Meter)

DDSU666 5(80)A, DDSU666 1.5(6)A Model(s):

Parameters: Rated voltage: 230VAC, 50/60Hz

> Rated current: DDSU666 5(80)A: max. 80A:

DDSU666 1.5(6)A: max. 6A

Overvoltage class: Class II Pollution degree: Ш

Means of protection: Class II

Tested EN 61010-1:2010 EN 61010-2-030:2010 according to:

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. See also notes overleaf.

Test report no.: 64105180109701

Frank Then

Date, 2018-04-11 (Frank Zhu)





After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.

Page 1 of 1

Declaration of Conformity

Hereby the manufacturer, **Guangzhou Sanjing Electric Co., Ltd.**, declares that the following model Load monitoring device:

SEC Kit - S80

SEC Kit - S100

SEC Kit - T80

SEC Kit - T100

SEC Kit - T250

Do fulfill the requirements defined defined in:

- European Parliament and Council Directive 2011/65/EU on the Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment (ROHS).
- The BBP/DBP/DEHP/DIBP content requirements of the European Council Directive 2011/65/EU on the Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment (ROHS) with its Amendments Directive 2015/863.
- Directive 2014/53/EU of the European Parliament and of the Council on the use of radio equipment. (RED).

Guangzhou Sanjing Electric Co., Ltd.

No. 9, Lizhishan Road, Science City, Guangzhou High-tech Zone, Guangdong, P.R. China

Signature:

Date: April 1, 2022



Certificate of Conformity

Certificate Number: CN-PV-190092

On the basis of the tests undertaken, the samples of the below product have been found to comply with the requirements of the referenced specification/standard at the time the tests were carried out. It does not imply that Intertek has performed any surveillance or control of the manufacture. The manufacturer shall ensure that the manufacturing process assures compliance of the production units with the examined products mentioned in this certificate.

Applicant: Guangzhou Sanjing Electric Co., Ltd.

No.9, Lizhishan Road, Science City, Guangzhou High-tech Zone, Guangdong,

P.R.China

Product: Anti-backflow system

Ratings & Principle See Annex to Certificate of Conformity
Characteristics:

Model: PV Grid-connected Inverter:

R5-3K-S2, R5-4K-S2, R5-5K-S2, R5-6K-S2, R5-7K-S2, R5-8K-S2 R5-0.7K-S1, R5-1K-S1, R5-1.5K-S1, R5-2K-S1, R5-2.5K-S1, R5-3K-S1

Wattmeter: DDSU666

Brand Name:

Tested according to: UNE 217001 IN: October 2015

Requirements and tests for systems intended to avoid the

energy transmission to the distribution network

Certificate Issuing Office Name &

Address:

Intertek Testing Services Ltd. Shanghai

2/F (West Side), No. 707, Zhangyang Road, Free Trade Experimental Area, Shanghai,

SFT-PV-OP-23a (29-August-2019)

P. R. China

Test Report No.:

191115098GZU-001

Additional information in Appendix.

Signature

Certification Manager: Grady Ye

/ susta

Date: 24 December 2019



APPENDIX: Certificate of Conformity

This is an Appendix to Certificate of Conformity Number: CN-PV-190092

Ratings & Principle Characteristics:

PV Grid-connected Inverter:

Model	R5-3K- S2	R5-4K- S2	R5-5K- S2	R5-6K- S2	R5-7K- S2	R5-8K- S2			
Max Voltage	600 Vdc								
MPPT voltage range	90-550 Vdc								
Max DC input Current [PV1/PV2]		12.5/1	25/12.5 Adc						
Max. Short circuit Current [PV1/PV2]	Ť	15/1	30/15Adc						
Nominal AC voltage	230Vac								
Rated AC current [A]	13.1	17.4	21.8	26.1	30.5	34.8			
Max.AC Current [A]	14.4	19.2	24.0	26.1	33.5	34.8			
Grid Frequency	50Hz								
Rated Power [W]	3000	4000	5000	6000	7000	8000			
Max. AC power [VA]	3300	4400	5500	6000	7700	8000			
Power factor	0.8 Leading to 0.8 Lagging								
Temperature	-40°C - +60°C								
Protective Class	Class I								
Ingress protection	IP 65								
Software Version	V1.142								



APPENDIX: Certificate of Conformity

This is an Appendix to Certificate of Conformity Number: CN-PV-190092

Ratings & Principle Characteristics:

Model	R5- 0.7K- S1	R5-1K- S1	R5- 1.5K- S1	R5-2K- S1	R5- 2.5K- S1	R5-3K- S1		
Max Voltage	450 Vdc			500 Vdc				
MPPT voltage range	40-425 Vdc			50-450 Vdc				
Max DC input Current	12.5 Adc							
Max. Short circuit Current	15Adc							
Nominal AC voltage	230Vac							
Rated AC current [A]	3.1	4.4	6.6	8.7	10.9	13.1		
Max.AC Current [A]	3.5	5.0	7.5	10.0	12.5	15.0		
Grid Frequency	50Hz							
Rated Power [W]	700	1000	1500	2000	2500	3000		
Max. AC power [VA]	770	1100	1650	2200	2750	3300		
Power factor	0.8 Leading to 0.8 Lagging							
Temperature	-40°C - +60°C							
Protective Class	Class I							
Ingress protection	IP 65							
Software Version	V1.142							



APPENDIX: Certificate of Conformity

This is an Appendix to Certificate of Conformity Number: CN-PV-190092

Ratings & Principle Characteristics:

Wattmeter:

Voltage: AC 220/230V Current (CT): 100A/40mA Frequency: 50/60Hz

Class of Power measurement: Class I Type of communication: RS485

Operational temperature: -40°C - +60°C

Ingress protection: IP 54

Software Version: control: V1.146, communication: V2.027